



High Performance Microchannel Condensers

API Heat Transfer is a major supplier of all aluminum parallel flow condensers using extruded tubes. Brazed aluminum provides highly efficient, robust designs using lightweight all aluminum materials.



45%
Less Refrigerant

Compared to F&T. Significant cost savings.

29%
Smaller

Compared to F&T.

33%
Lighter

Compared to F&T.

Features



- ✔ Manufactured in the USA
- ✔ Multi-port extrusion for enhanced performance and pressure capability
- ✔ Versatile Mounting Style
- ✔ With or Without Brackets
- ✔ Convenient Sizes
- ✔ Lightweight Aluminum Construction
- ✔ Low Air Side Pressure Drop
- ✔ O-Ring Style Tube Fittings
- ✔ 2, 3 or 4 Pass Designs Available
- ✔ Customization Available Upon Request
- ✔ Furnace brazed for low leak potential compared to manually braze fin and tube

Technical

Temperature Range

-40° F to 240° F

Burst Pressure

1500 psi (1" thick core)

Capable Refrigerants

R134A, 454A, R1234yf, 407C, 410A, 454B

External Fin

14 - 20 fpi louvered (available for both depths)

Size Options

Core Depth

.71 / 1 in

Max Stack Height

34 in

Max Width

90 in header to header

Header Pipe

1 / 1.18 in



OEMSales

200 East Big Beaver Road, Troy, MI 48083
P: (248) 752-2620 | E: Sales@oemsalesinc.com